

GASCHECK™ LEAK DETECTORS

LHHLD-G3



GasCheck G3 Sniffer Leak Detectors are ideal for portable leak detection. The handheld design features a large backlit LCD display and battery operation. The GasCheck performs even in dark, confined spaces. Peak hold and auto-range settings offer maximum sensitivity and accurate readings of leak rates.

A microthermal conductivity sensor detects any gas different from air. Principally calibrated for helium, the unit can be set for gases such as Ammonia, Argon, Butane, Hydrogen, SF6 and some refrigerants.



GASCHECK LEAK DETECTORS	
MODEL	FEATURES
LHHLD-G3	<p>The newly-released LHHLD-G3 (GasCheck G3) is an upgrade to the LHHLD-3000 (GasCheck 3000). The new G3 features the following upgrades:</p> <ul style="list-style-type: none"> • Readings in ppm, cc/sec, or mg/m³ • Data logging of 10 points • New graphical icon display menu

GASCHECK SPECIFICATIONS

COMPONENT	DESCRIPTION
DETECTOR	Micro volume thermal conductivity cell
ACCURACY	+/- 5% Displayed reading - One digit
TEMPERATURE	-20 to 60°C
RESPONSE	1 second with 1 second clear downtime
DIMENSIONS	L = 15" x W = 2.5" x D = 2"
WEIGHT	With batteries 1.1 lb.
BATTERIES	4 AA supplied; 40 hour life (typical unit)
SENSITIVITY	He = 1x10 ⁻⁵ R-12 = 8x10 ⁻⁵ Ar = 1x10 ⁻⁴ CH ₄ = 1x10 ⁻⁴

APPLICATIONS

- Quality Assurance Testing on Component Seals
- Membrane Materials & Glove Boxes
- Stored Gases & Chemicals
- Gas Cylinders & Fittings
- Gas Chromatographs
- Mass Spectrometers
- Gas Installations
- Pipeline Assemblies
- Anaesthetic Gas Bottles
- Valve Emission Evaluation
- Pipeline Joints, Gaskets & Chamber Windows



Available on our *Try Before You Buy* program. Call us to learn more.